

www.erm-automatismes.com

ErmaSmart #5

Dynamic Vertical Store

Dynamic storage and retrieval system for trays or boxes/pallets

Description of the system

The Dynamic Vertical Warehouse system is an automated customer order picking system. It ensures the dynamic storage and retrieval of trays or boxes/pallets. In order to prepare an order, it can combine stored trays or boxes/pallets with just-in-time produced trays or boxes/pallets. It thus allows to approach the notions of stock, minimum production quantity, just-in-time...

It incorporates a system of 2 XZ Cartesian axes, which are often used in industrial vertical warehouses. The functions and components are based on real industrial components used in the logistics industry.

This Dynamic Vertical Warehouse system (ref VL10) designed in the spirit of the industry of the future (Industry 4.0) meets the main requirements on intelligence and the evolution of production methods:

- Flexibility & customisation with the possibility of unvidual order picking
- IoT & Communications with RFID tag reading/writing for identification and tracking of customer order packages.

This automated system can be used independently with trays or boxes/pallets, but can also be integrated into the flexible ErmaSmart production line (see p. 3 and 4).

The main functions of the Dynamic Vertical Store (VL10) are:

- Convey the trays or boxes/pallets from the infeed to the pick-up station, and possibly let them go to the conveyor outfeed in case of just-in-time production
- ✓ Place the trays or boxes/pallets in the indicated vertical shop location by associating the RFID number of the trays or boxes/pallets with the product type and the storage location in the shop
- Retrieve trays or boxes/pallets from the registered bins to prepare an order with stock, checking that the RFID number of the tray or box/pallet entered is the one requested
- Remove trays or boxes/pallets to the exit

This training system is mainly intended for activities in the fields of operation, system control, industrial maintenance, electrical engineering, automation and mechanics.

This product is accompanied by a technical and educational file in digital format.

CAP CIP - Bac PRO PLP / MELEC / MSPC BTS CRSA / Electrical engineering / MS

Main Themes

Industrial Maintenance Production Control Multi-technology Systems Design **Electrical Engineering and Automation**



Scalability & Flexibility



Efficient Actuators

Digital instructions & MES

Vision & Smart Sensors

IOT & Communications

Additive manufacturing for tooling...

More information on www.erm-automatismes.com

Highlights

- Real industrial system with modern technologies (XZ Cartesian robot, IO-Link, Ethernet, Profinet, RFID...)
- Production flexibility with the storage of different trays and boxes/pallets
- Traceability of the customer's order with the writing and reading of RFID tags
- Introduction to industrial logistics techniques
- System usable in the fields of electrical engineering, industrial maintenance, and the operation and piloting of automated systems
- Includes Siemens Tia Portal programming software for programming the PLC and the dialogue terminal
- IO-Link technology with IO-Link Profinet master (IFM brand) and MONEO Configure sensor visualization and
- setting software and IO-Link intelligent sensors (RFID, vacuum generator, photoelectric sensor...) Possible extensions to the ErmaSmart flexible production line





Overview





Solutions didactiques et technologiques

www.erm-automatismes.com

General

The Dynamic Vertical Store (Ref: VL10) consists mainly of :

- A welded frame with epoxy paint, fully enclosed on 4 castors with brakes.
- \checkmark An electrical cabinet with a man-machine interface (colour touch panel) fixed to the chassis
- ✓ An operating part with three main functional assemblies, the conveyor, the 2-axis XZ Cartesian robot and the gripper system.

Functional sub-assembly "Conveyor

It consists mainly of :

- ✓ A 9 m/min belt conveyor with edges
- A 230/400V 0.09 kW three-phase asynchronous geared motor controlled by a variable speed drive
- ✓ Two light curtains at the conveyor inlet and outlet
- A tray or box/pallet arrival station with a presence detector (Station 1) and an IO-Link RFID transceiver to read the information on the RFID tags of the trays or boxes/pallets
- ✓ A tray or box/pallet departure station with presence detector (Station 2) and IO-Link RFID transceiver to read and write information on the RFID tags of the trays or boxes/pallets
- ✓ An evacuation zone

Functional sub-assembly "XZ robot It consists mainly of :

- ✓ A two-axis XZ Cartesian robot with stepper motors incorporating an encoder, belt drive and greaseless linear guidance. The working area is approximately 1000 x 1600 mm with a load capacity of 20N
- ✓ Limit switches on both axes
- ✓ A suction cup gripping mechanism with energy-saving IO-Link vacuum generator

Functional sub-assembly "Gripping system It consists mainly of :

- A proportional pneumatic cylinder with IO-Link position sensor
- ✓ A suction cup gripper system with energy-saving IO-Link vacuum generator
- An IO-Link distance sensor (with on-board task) to monitor the presence of a tray or box/pallet in a location

Installation features

- VL10:
 - ✓ Dimensions (LWD): 2400 x 1100 x 2260 mm
 - ✓ Mass: 200 kg
 - ✓ Power supply: 230 V three-phase (P + N + T)
 - ✓ Pneumatic supply: 7 bar

Electrical control / command cabinet

It consists mainly of :

- ✓ A padlockable disconnect switch
- \checkmark A set of electrical protections
- \checkmark A safety relay, an emergency stop button and a system reset button
- ✓ A Siemens S7-1200 PLC (or optional S7-1500)
- ✓ A Siemens SIMATIC HMI KTP700 Basic (7 inch) colour touch screen Human Machine Interface
- A switch to ensure communication between the PLC, the HMI and the connected environments
- ✓ An IO-Link Profinet master (IFM brand) and MONEO Configure sensor visualization and setting software
- ✓ A variable speed drive for the conveyor
- \checkmark Two axis control boards for the stepper motors of both XZ axes
- An area dedicated to the electrical wiring of new components in the context of system improvements (new sensors, actuators, etc.)



Light curtain at the conveyor entrance





Controller Industrial S7-1200

and the set

Human Machine Interface Siemens HMI KTP700 Basic

visualisation and setting software



www.erm-automatismes.com

Dynamic Vertical Store Station 5 of the ErmaSmart flexible production line "Packaging

ErmaSmart Item 5 "Packaging

In the **ErmaSmart "Packaging"** context, the Dynamic Vertical Store is used for dynamic storage and retrieval of trays, as well as order picking. Upstream of the Dynamic Vertical Store are:

- Station 1: The 2D Unscrambling & Screwing Robot, 2D/3D jar/flask unscrambling and conveyor placement system (ref ON10 and associated codes)
- Item 2: The Dosaxe, automatic linear axis filling system (ref DX10 and associated codes)
- Station 3: The Collaborative Robot Capping & Assembly system for capping, custom overcapping and control (ref MI00 and associated codes)
- Item 4: The XYZ Cartesian Pick&Place (ref XY10 and associated codes)

Downstream from the Dynamic Vertical Store is:

• Station 6: The manual order picking, packing and palletising station with RFID tracking (ref PM91).

ErmaSmart Configuration "Conditioning

In the ErmaSmart "Packaging" configuration, the Dynamic Vertical Magazine provides storage and order picking of trays.

This configuration requires the codes:

VL10 : Dynamic Vertical Magazine with tray gripping and storage module

Combined operation with AGV(+Arm)

Ermasmart offers the combined use of the Dynamic Vertical Warehouse and the MiR100 AGV with UR eSeries collaborative arm. These two systems communicate with each other so that the AGV+Arm can autonomously retrieve boxes/tray from an order at the exit of the

conveyor or load the Dynamic Vertical Magazine with component boxes (Stand alone version). If the AGV is not equipped with an arm, an operator will have to perform

the handling operations between the AGV and the Dynamic Vertical Warehouse.

Dynamic Vertical Warehouse integrated into the ErmaSmart Industry 4.0 Factory "Packaging





www.erm-automatismes.com

Dynamic Vertical Store Station 4 of the ErmaSmart flexible production line "Assembly

ErmaSmart Station 5 "Assembly

In the **ErmaSmart "Packaging"** context, the Dynamic Vertical Store is used for dynamic storage and retrieval of trays, as well as order picking. Upstream of the Dynamic Vertical Store are:

- Item 1: The XYZ Cartesian Pick&Place (ref XY10 and associated codes)
- Station 2: The Collaborative Capping & Assembly Robot, customised assembly system and control (ref MI00 and associated codes)
- Station 3: The 2D Unscrambling & Assembly-Screwing collaborative robot, assembly and screwing system (ref ON10 and associated codes)

Downstream from the Dynamic Vertical Store is:

• Station 5: The manual order picking, packing and palletising station with RFID tracking (ref PM91).

ErmaSmart Configuration "Assembly

In the ErmaSmart "Assembly" configuration, the Dynamic Vertical Warehouse provides storage and order picking of boxes/pallets.

- This configuration requires the codes:
 - VL10: Dynamic Vertical Warehouse with box/pallet picking and storage module

Combined operation with AGV(+Arm)

Ermasmart offers the combined use of the Dynamic Vertical Warehouse and the MiR100 AGV with UR eSeries collaborative arm. These two systems communicate with each other so that the AGV+Arm can autonomously retrieve boxes/tray from an order at the exit of the conveyor or load the Dynamic Vertical Magazine with component boxes (Stand alone version).

If the AGV is not equipped with an arm, an operator will have to perform the handling operations between the AGV and the Dynamic Vertical Warehouse.

Dynamic Vertical Warehouse integrated into the ErmaSmart Industry 4.0 Factory "Assembly





Solutions didactiques et technologiques

www.erm-automatismes.com

Educational activities

The Dynamic Vertical Store system allows the following educational activities to be carried out

- ✓ Electrical engineering
 - Discovery and handling of the system (functional analysis and study of system technologies)
 - Control of the system's electrical quantities (network, power supply, drive, XZ axis controls, PLC, HMI and control circuit).
 - Commissioning and validation of the system operation (of the different production modes)
 - Adjustment and parameterisation of the installation components (asynchronous geared motor and its frequency converter, XZ axis control)
 - Wiring of new sensors and actuators (improvement and/or replacement of an electrical component of the installation)
 - **Programming of** new cycles of the PLC and the Human Machine Interface (TIA Portal software supplied).
 - Diagnosis of a malfunction or malfunctions
 - Use of digital tools and communication
- ✓ Automation
 - Functional and structural analysis of the system
 - Programming the Vertical Magazine Axis Controls
 - **Programming of production cycles** (TIA Portal software delivered with the system)
 - Programming of the human machine interface (TIA Portal

- software delivered with the system)
- Implementation of IO-Link sensors (Reassignment of inputs/outputs...) and IO-Link vacuum generator

Production control

- Production control with choice of packaging method (in cartons or trays)
- Change of production format
- Traceability and logistics with RFID tag writing
- Development of operator support procedures
- Optimising production with digital 4.0 tools
- ✓ Industrial maintenance
 - Preventive maintenance (conveyors, suction, etc.)
 - Corrective maintenance (fault diagnosis using the TIA PORTAL basic software delivered with the cell, rapid manufacture of 3D printing tools, etc.)
 - Improved maintenance (addition of sensors on the conveyor, new format of boxes, trays,...)
- ✓ Mechanics
 - Study of a station with linear axes, ergonomics, dimensioning of axes and actuators...
 - · Design of 3D printed parts

References

VL10: Dynamic Vertical Magazine with Pick and Place module for trays (ErmaSmart "Packaging"), boxes/pallets (ErmaSmart "Assembly") and standard component boxes (Stand alone version)

UC90 : Option: Fault box for electrical box, remotely configurable on a tablet (Not supplied)

UC51 : Option: Visual instructions & Monitoring of production indicators on the Tulip open application environment and touchscreen tablet, for one machine (with a 3-year subscription to Tulip Pro, €1170 excl. tax per year beyond that)

UC52 : Option: Visual instructions on the Tulip open application environment and touchscreen tablet, for one machine (with a 3-year subscription to Tulip Standard, €570 excl. tax per year beyond that)

UC41: Siemens Remote Desk Option on iPad (Included)

IO01: Option: Electrical and pneumatic measurement sensors (IO-Link) for monitoring the power, flow and electrical and pneumatic consumption of a machine equipped with an IO-Link master and supervision and preventive maintenance software



Visual instructions & Monitoring of production indicators on the Tulip open application environment and touchscreen tablet, for one machine (With a 3-year subscription to Tulip Pro, €1170 excl. tax per year beyond that) (Ref: UC51)



Electrical and pneumatic measurement sensors (IO-Link) for monitoring the power, flow and electrical and pneumatic consumption of a machine equipped with an IO-Link master (Ref: IO01)

Diota" Augmented Reality Scenario available







From the CAD/PLM tool (Solidworks Composer) to the industrial maintenance RA scenario job card DF10: Industrial augmented reality solution DIOTA Tablet